

# MARIAFLORA

ITALIAN LUXURY PERFORMANCE FABRICS

## RODRIGO 10457

Composition: 100% Trevira CS

Width: 138cm /54"

Weight: 790 gr/m - 25,4 oz/yd

H rep: /

V rep: /

Martindale: 50.000

Light fastness: 7/8

Fire rating:

Mariaflora Trevira CS fabrics pass:

DIN 4102, DIM 4102-B1

EN 1021 – 1+2

BS 5852 CRIB5

IMO part 7

IMO part 8



Flame  
retardant



Crib 5



IMO



in-outdoor



water  
repellent



stain resistant

## Cleaning instructions:


Under normal conditions Mariaflora fabrics woven in Trevira can be hand-or machine-washed with a gentle 30°C (86°F) cycle and a soft detergent.

Low speed spin dry, then air dry.

Avoid using tumble dryers.

Trevira fabrics do not withstand the harshness of chlorine bleach or strong chemicals.

Professional dry cleaning is always recommended





## Approval of the Trademark Trevira CS®

Filippo Uecher S.r.l.  
Via Leonardo da Vinci, 5  
13854 QUAREGNA BI  
Italy

<b>Application No.:</b>	191221
<b>Date of issue:</b>	20.11.2019
<b>Valid until:</b>	20.11.2024
<b>Article name:</b>	Rodrigo 10457
<b>End use:</b>	Drapes Upholstery fabrics Wall coverings
<b>Square weight (g/m<sup>2</sup>):</b> According to customer specification	560
<b>Composition of fabric:</b>	Polyester 100% Trevira CS
<b>Yarn:</b>	Warp, 2 / 10 Nm Trevira® Type Trevira CS, Yarn supplier Tintoria Sala S.r.l. Weft, 2 / 10 Nm Trevira® Type Trevira CS, Yarn supplier Tintoria Sala S.r.l.

The tested article Rodrigo 10457 col.130 with application no. 191221 is granted approval for the trademark Trevira CS® for interior use. This article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

This article has been tested according to the French standard NF P 92-503 (Brûleur électrique) and has reached class M3.

The article was tested according to EN 1101 and thus also meets the requirements for class 1 according to EN 13773.

This article meets the requirements according to EN 1021 part 1+2 in conjunction with polyurethan foams with a density of more than 30 kg/m<sup>3</sup>.

Thus meets also the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (match) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m<sup>3</sup>).

This article also meets the requirements for class I according to the North American standard NFPA 260 for upholstered furniture (based on the Test Reports no. 10-002-775 A + B dated 24.11.2010).

Trevira GmbH  
(This document is valid without signature.)